


**Features**

- Extremely wide measuring range
- Excellent measuring accuracy
- Custom flooring material
- Floor integration options
- Built-in amplifier with acquisition system
- Start and stop triggers
- LAN connection
- Control & acquisition software included
- Real-time user feedback
- Cost-effective

**Applications**

- Biomechanics
- Research
- Posture and movement analysis
- Jump analysis

Overview		
Model	3D-force plate 600450	
Dimensions	600 x 450 x 80 mm	
Overload range	Fx, Fy, Fz	15 kN
Interfaces	Ethernet interface Two inputs and one output digital trigger Analog force output Status LED	

Construction	
Sensors	Strain gauge / Aluminum
Top plate	Aluminum
Bottom plate	Aluminum
Options	Flooring support plate, Aluminum base plate, Multi-plate interconnection enclosures

Performance		
Linearity	Fx, Fy	<0.1 %
	Fz	<0.1 %
Hysteresis	Fx, Fy	<0.1 %
	Fz	<0.1 %
Cross-talk	Fz → Fx, Fy	<0.3 %
Drift	Fx, Fy, Fz	<1 N / h
Natural frequency	x-axis	> 270 Hz
	y-axis	> 270 Hz
	z-axis	> 340 Hz

Physical	
Mass	24 kg
Operating / storage temperature	10 ... 40°C / -25 ... 40°C
Operating / storage humidity	30 ... 70% (non condensing) / 0 ... 95% (non condensing)
Ingress protection	IP 00
Air pressure	700 ... 1060 hPa (max 3000m altitude)
Anchorage	8 x M8 captive screws

Electrical	
Supply voltage	85-264 VAC, 47-440 Hz
Power consumption	10W
Fuse	500 mA

Amplification																									
Amplifier	8 channels: 4x Fz, 2x Fy, 2x Fx																								
Analog filter	Bessel 4-pole low pass filter (cut-off frequency: 85 Hz)																								
Measuring range	Adjustable upon request																								
	<table border="1"> <thead> <tr> <th></th> <th>Min.</th> <th>Default range</th> <th>Max.</th> </tr> </thead> <tbody> <tr> <td>Measuring range on each sensor</td> <td>Fx Fy Fz</td> <td><math>\pm 0.1</math> kN <math>\pm 0.1</math> kN 0.1 kN</td> <td><math>\pm 0.9</math> kN <math>\pm 1.2</math> kN 3.3 kN</td> <td><math>\pm 7.2</math> kN <math>\pm 9.4</math> kN 6.7 kN</td> </tr> <tr> <td>Resolution</td> <td>Fx Fy Fz</td> <td>7 mN 9 mN 4 mN</td> <td>60 mN 80 mN 140 mN</td> <td>460 mN 600 mN 280 mN</td> </tr> <tr> <td>Noise (peak-to-peak)</td> <td>Fx Fy Fz</td> <td><math>\pm 0.2</math> N <math>\pm 0.2</math> N <math>\pm 0.1</math> N</td> <td><math>\pm 0.2</math> N <math>\pm 0.2</math> N <math>\pm 0.6</math> N</td> <td><math>\pm 1.2</math> N <math>\pm 1.2</math> N <math>\pm 1.1</math> N</td> </tr> <tr> <td>Sensitivity at analog interface</td> <td>Fx Fy Fz</td> <td>24 N/V 31 N/V 14 N/V</td> <td>190 N/V 250 N/V 460 N/V</td> <td>1510 N/V 1970 N/V 920 N/V</td> </tr> </tbody> </table>		Min.	Default range	Max.	Measuring range on each sensor	Fx Fy Fz	$\pm 0.1$ kN $\pm 0.1$ kN 0.1 kN	$\pm 0.9$ kN $\pm 1.2$ kN 3.3 kN	$\pm 7.2$ kN $\pm 9.4$ kN 6.7 kN	Resolution	Fx Fy Fz	7 mN 9 mN 4 mN	60 mN 80 mN 140 mN	460 mN 600 mN 280 mN	Noise (peak-to-peak)	Fx Fy Fz	$\pm 0.2$ N $\pm 0.2$ N $\pm 0.1$ N	$\pm 0.2$ N $\pm 0.2$ N $\pm 0.6$ N	$\pm 1.2$ N $\pm 1.2$ N $\pm 1.1$ N	Sensitivity at analog interface	Fx Fy Fz	24 N/V 31 N/V 14 N/V	190 N/V 250 N/V 460 N/V	1510 N/V 1970 N/V 920 N/V
	Min.	Default range	Max.																						
Measuring range on each sensor	Fx Fy Fz	$\pm 0.1$ kN $\pm 0.1$ kN 0.1 kN	$\pm 0.9$ kN $\pm 1.2$ kN 3.3 kN	$\pm 7.2$ kN $\pm 9.4$ kN 6.7 kN																					
Resolution	Fx Fy Fz	7 mN 9 mN 4 mN	60 mN 80 mN 140 mN	460 mN 600 mN 280 mN																					
Noise (peak-to-peak)	Fx Fy Fz	$\pm 0.2$ N $\pm 0.2$ N $\pm 0.1$ N	$\pm 0.2$ N $\pm 0.2$ N $\pm 0.6$ N	$\pm 1.2$ N $\pm 1.2$ N $\pm 1.1$ N																					
Sensitivity at analog interface	Fx Fy Fz	24 N/V 31 N/V 14 N/V	190 N/V 250 N/V 460 N/V	1510 N/V 1970 N/V 920 N/V																					

Ethernet interface	
Connector	RJ-45
Speed	10 / 100 Mbit/s
Analog-to-digital converter	Built-in, 8 channels, 16-bit resolution, simultaneous sampling
Sampling rate	100Hz ... 10 kHz

Digital interface		
Trigger input	BNC	5V digital TTL/CMOS, isolated
Aux input	BNC	5V digital TTL/CMOS, isolated
Sync output	BNC	5V digital TTL/CMOS, isolated
Zero input	BNC	5V digital TTL/CMOS, isolated

Analog output		
Connector		15-pin sub-D HD
Output channels		8 channels: 4x Fz, 2x Fy, 2x Fx
Output range	Fx, Fy, Fz	0 to 10 V
Output type	Fx, Fy, Fz	Single-ended ground referenced

Software	
Data acquisition	3D-ForcePlate©
Functions	Force & center of pressure monitoring, Configuration, Data acquisition and storage, Visualization of acquired data, Video recording, Computation of forces, moments and center of pressure.
Compatibility	Windows 10 / 11
Export file format	Native binary, tab delimited text
Software options	Digital data streaming, Decomposition of left & right foot forces for double stance on a single force-plate, Ethernet client for Vicon Nexus, Qualisys QTM, Noraxon MR3.